



## Mezza campanella (chiusa) tipo SKG




Tipo	Portata max ton*	Per catene di mm	Dim. in mm			Peso appr. Kg
			L	B	G	
SKG-7/8-8	2,0	7,8	99	50	14	0,3
SKG-10-8	3,2	10	127	66	18	0,6
SKG-13-8	5,4	13	145	72	22	1,1
SKG-16-8	8,0	16	175	82	25	1,7
SKG-18/20-8	12,5	19	204	105	30	2,8

## Tornichetto isolato tipo SKLI




Tipo	Portata max ton*	Per catene di mm	Dim. in mm		Peso appr. Kg
			L	D	
SKLI-7/8-8	2,0	7,8	75	48	0,7
SKLI-10-8	3,15	10	96	59	1,4
SKLI-13-8	5,3	13	120	75	2,9
SKLI-16-8	8,0	16	137	90	4,9
SKLI-18/20-8	12,5	19	159	104	7,2

## Giunto per catene Berglok tipo BLL




Tipo	Portata max ton*	Per catene di mm	Dim. in mm				Peso appr. Kg
			L	B	G	H	
BLL-7/8-8	2,0	7,8	35	25	11	18	0,2
BLL-10-8	3,2	10	45	32	14	22	0,4
BLL-13-8	5,4	13	56	40	17	28	1,0
BLL-16-8	8,0	16	68	50	22	35	1,4
BLL-19-8	11,5	19	80	58	25	41	2,3

## Gancio bloccamaglia tipo GGL



Tipo	Portata max ton*	Per catene di mm	Dim. in mm		Peso appr. Kg
			L	B	
GGL-7-8	1,5	7	56	10	0,3
GGL-10-8	3,2	10	78	13	0,8
GGL-13-8	5,4	13	97	16	1,5
GGL-16-8	8,0	16	124	20	2,8

## Gancio bloccamaglia tipo OGL



Tipo	Portata max ton*	Per catene di mm	Dim. in mm				Peso appr. Kg
			L	B	E	F	
OGL-7-8	1,5	7	60	10	15	9	0,2
OGL-8-8	2,0	8	70	11	16	10	0,4
OGL-10-8	3,2	10	84	13	20	12	0,6
OGL-13-8	5,4	13	104	16	25	15	1,2
OGL-16-8	8,0	16	130	20	28	19	2,4
OGL-19-8	11,5	19	156	25	36	23	4,6
OGL-22-8	15,5	22	181	29	42	26	8,2

La sicurezza nel sollevamento con catene e componenti