



Gancio con linguetta tipo EKN



Tipo	Portata max ton*	Per catene di mm	Dim. in mm						Peso appr. Kg
			L	B	E	F	G	H	
EKN-6-8	1,12	6	94	24	22	10	16	19	0,3
EKN-7/8-8	2,0	7,8	105	28	25	11,5	17	22	0,5
EKN-10-8	3,15	10	131	37	32	13,5	19	29	0,9
EKN-13-8	5,3	13	161	42	40	17,5	27	36	1,8
EKN-16-8	8,0	16	197	52	50	22	34	44	3,4
EKN-18/20-8	12,5	19	229	60	60	26	37	52	5,1
EKN-22-8	15,0	22	267	77	64	31	42	67	8,9

Gancio per braghe con linguetta tipo GKNL



Tipo	Portata max ton*	Per catene di mm	Dim. in mm				Peso appr. Kg
			L	B	G	H	
GKNL-7/8-8	2,0	7,8	86	25	19	32	1
GKNL-10-8	3,2	10	104	34	23	36	1,8
GKNL-13-8	5,3	13	128	41,5	30	43	2,9
GKNL-16-8	8,0	16	154	57,5	36	51	4,8
GKNL-20-8	11,5	19	185	63	44	64	5,4

Gancio di sicurezza con sicura ad incastro tipo OBKL




Tipo	Portata max ton*	Per catene di mm	Dim. in mm						Peso appr. Kg
			L	B	E	F	G	H	
OBKL-7/8-8	2,0	7,8	137	36	25	11	17	23	0,7
OBKL-10-8	3,2	10	168	44	32	13	25	29	1,5
OBKL-13-8	5,4	13	208	54	40	16	28	38	2,7
OBKL-16-8	8,0	16	254	63	50	20	37	49	5,6

Gancio di sicurezza tipo BKGL



Tipo	Portata max ton*	Per catene di mm	Dim. in mm				Peso appr. Kg
			L	B	G	H	
BKGL-7/8-8	2,0	7,8	120	35	20	25	0,8
BKGL-10-8	3,2	10	153	48	28	3,8	1,5
BKGL-13-8	5,4	13	192	56	31	39	2,8
BKGL-16-8	8,0	16	210	70	40	52	5,1

Gancio per fonderia tipo OKE



Tipo	Portata max ton*	Per catene di mm	Dim. in mm						Peso appr. Kg
			L	B	E	F	G	H	
OKE-7/8-8	2,0	7,8	122	63	25	11	18	26	0,6
OKE-10-8	3,2	10	150	76	32	14	23	30	1,1
OKE-13-8	5,4	13	182	90	40	18	32	38	2,3
OKE-16-8	8,0	16	215	102	50	22	40	45	3,8
OKE-18/20-8	12,5	19	247	114	60	26	45	50	6,0
OKE-26-8	21,6	26	300	113	66	38	64	73	17
OKE-32-8	32,0	32	384	145	80	48	77	94	35